

MATERIAL SAFETY DATA SHEET

Section 1: Product & Company Identification

Product Name: Power Lube® Multi-Purpose Lubricant - Aerosol
Product Number (s): 05003, 05005, 05005-6, 05005P, 05005T, 05006, 75005, 85005

Manufactured By: CRC Industries, Inc. (215) 674-4300
885 Louis Drive, Warminster, PA 18974
24-Hour Emergency Information: CHEMTREC (800) 424-9300

Section 2: Composition/Information on Ingredients

| Component | CAS NUMBER | ACGIH TLV | OSHA PEL | OTHER LIMITS | % |
|--------------------------|-------------------|---------------------|---------------------|--------------|-------|
| Petroleum Distillate | 64742-47-8 | NE | 400 ppm | 100 ppm | 50-80 |
| Inhibited Paraffinic Oil | Proprietary Blend | 5 mg/m ³ | 5 mg/m ³ | (mist) | 1-30 |
| Carbon Dioxide | 124-38-9 | 5000 ppm | 10000 ppm | NE | 1-10 |

Section 3: Hazards Identification

Emergency Overview

Appearance & Odor: Amber liquid, pleasant odor.

Danger: Flammable. Harmful or Fatal if Swallowed. Contents Under Pressure.

Potential Health Effects:

Inhalation: Headaches, nausea, dizziness and breathing problems.
Eyes: Irritation, burning
Skin: Dryness
Ingestion: NA

Carcinogenicity: OSHA: No IARC: No NTP: No
Chronic Overexposure: Dermatitis.
Medical Conditions Aggravated by Exposure: NA

Section 4: First Aid Measures

Inhalation: Remove to fresh air. Give artificial respiration if necessary.
Eyes: Flush with large amounts of water for 15 minutes.
Skin: Remove contaminated clothing and wash area with soap and water.
Ingestion: Call a physician. Do not induce vomiting.

Product Name: Power Lube® Multi-Purpose Lubricant - Aerosol
Product Number (s): 05003, 05005, 05005-6, 05005P, 05005T, 05006, 75005, 85005

Section 5: Fire-Fighting Measures

Flashpoint: 165°F Method: TCC LEL: ND UEL: ND
Extinguishing Media: CO₂, dry chemical and foam
Hazardous Combustion Products: CO₂ and carbon monoxide (fire)
Fire-fighting Instructions: Remove containers from fire area if possible. Use self-contained breathing apparatus for fire fighting. Aerosol cans may explode if heated above 120°F.
NFPA: Health: 1 Flammability: 2 Reactivity: 0
HMIS: Health: 1 Flammability: 2 Reactivity: 0 PPE: B

Section 6: Accidental Release Measures

Spill/Leak Procedures: Usually not a problem with aerosols. Area should be ventilated. Absorbent should be used to pick up excess material. All used and unused product should be disposed of in accordance with federal, state and local regulations.

Section 7: Handling and Storage

Handling Procedures: Store in a cool, dry area. Aerosol cans must be maintained below 120°F to prevent cans from exploding.

Aerosol Level: III

Section 8: Exposure Controls/Personal Protection

Engineering Controls: Adequate to prevent accumulation of vapors. Use mechanical means if necessary to maintain levels below the exposure limits. If working in a confined space, follow applicable OSHA regulations.

Respiratory: Use NIOSH/MSHA compliant respirators or self-contained breathing apparatus above exposure limits. Follow OSHA regulations 29 CFR 1910.134.

Protective Clothing/Equipment: Wear chemically protective gloves and safety glasses. Use a splash apron and boots if splashing occurs.

Section 9: Physical & Chemical Properties

| | | | |
|-------------------------------|----------------------|-------------------------|-----------------------------|
| Physical State: | Liquid | Appearance & Odor: | Amber liquid, pleasant odor |
| Specific Gravity: | 0.8223 | Boiling Point: | 380°F (initial) |
| Freezing Point: | ND | Vapor Pressure: | 0.23 mm |
| Evaporation Rate: | slow .01 (toluene=1) | Vapor Density (air = 1) | > air |
| pH: | NA | Solubility: | Negligible in water |
| Volatile Organic Compounds %: | 50 | g/L: 398 | lbs./gal: 3.32 |

Section 10: Stability and Reactivity

| | | | |
|-----------------------------------|-------------------|---------------------------|----|
| Stability: | Stable | Hazardous Polymerization: | No |
| Chemical Incompatibilities: | Strong oxidizers. | | |
| Materials to Avoid: | Strong oxidizers. | | |
| Hazardous Decomposition Products: | None | | |

Product Name: Power Lube® Multi-Purpose Lubricant - Aerosol
Product Number (s): 05003, 05005, 05005-6, 05005P, 05005T, 05006, 75005, 85005

Section 11: Toxicological Information

Long-term toxicological studies have not been conducted for this product. See Section 3 of this MSDS for acute symptoms of overexposure and carcinogenicity information.

Section 12: Ecological Information

Ecotoxicity: No data available.
Environmental Fate: No data available for biodegradation.

Section 13: Disposal Considerations

Disposal: This material if discarded may be hazardous waste under U.S. EPA RCRA regulations. All disposal activities must comply with federal, state and local regulations. Contact your local or state environmental agency for specific rules. Do not dump into sewers, on the ground or into any body of water.

Section 14: Transportation Information

Shipping Name: Consumer Commodity
Hazard Class: ORM-D UN Number: NA Packing Group: NA
Label: NA Placard: NA
Special Provisions: NA

Section 15: Regulatory Information

TSCA: All components are either listed under TSCA or are exempt.
SARA Title III: Section 311/312: Acute/Pressure Section 313*: None
CERCLA/Superfund (RQ): NA
Extremely Hazardous Substances: No
California Prop 65: NA

* See section 2 for percentage

Section 16: Additional Information

Prepared By: Michelle Milburn Date: November 16, 2004
Technical Information: (800) 521-3168 CRC #: 462D

This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label.

CAS: Chemical Abstract Service NA: Not Applicable
ppm: Parts per Million ND: Not Determined
TCC: Tag Closed Cup NE: Not Established
LEL: Lower Explosive Limit g/L: grams per Liter
UEL: Upper Explosive Limit lbs./gal: pounds per gallon
PPE: Personal Protection Equipment RQ: Reportable Quantity
COC: Cleveland Closed Cup